# Bernat In the Details Knit Hoodie Free Pattern



# **Pattern Description:**

An **easy skill level** knitting pattern for a baby hoodie. It includes instructions for the back, right and left fronts with pockets, sleeves, and a hooded panel. The pattern is designed for various baby sizes, from 6 to 24 months.

## **Materials Needed & Measurements:**

- Yarn: Bernat® Baby Blanket Tiny<sup>TM</sup> (14005 Tea Rose), 2 balls for all sizes.
- **Yarn Weight:** 3.5 oz/100 g; 316 yds /288 m.
- **Needles:** Size U.S. 6 (4 mm) knitting needles.
- **Circular Needle:** Size U.S. 6 (4 mm) circular knitting needle 29" [74 cm] long or size needed to obtain gauge.
- **Notions:** 2 stitch holders, Stitch markers, 3 buttons.
- Measurements:
  - **o** To fit chest measurement:
    - **6 mos:** 17" [43 cm]
    - **12 mos:** 18" [45.5 cm]
    - **18 mos:** 19" [48.5 cm]
    - **24 mos:** 20" [51 cm]

#### Finished chest:

6 mos: 19¾" [50 cm]
12 mos: 20¾" [52.5 cm]
18 mos: 21¾" [55 cm]
24 mos: 22½" [57 cm]

o **Gauge:** 17 sts and 36 rows = 4'' [10 cm] in garter stitch.

#### **Stitches & Abbreviations Used:**

• **Approx:** Approximate(ly)

Beg: Begin(ning)Cont: Continue(ity)Dec: Decrease(ing)

• **K**: Knit

• **K2tog:** Knit next 2 stitches together

• M1: Make 1 stitch by picking up horizontal loop lying before next stitch and knitting into back of loop

Pat: PatternRep: Repeat

• **Rem:** Remain(ing)

• **RS:** Right side

• St(s): Stitch(es)

• Wrap3: With yarn at back of work, slip next 3 stitches onto right-hand needle. Bring yarn to front of work and then slip same 3 stitches back onto left-hand needle. Take yarn in front of 3 stitches and to back of work, then (K2tog. yo. K1) same 3 stitches

WS: Wrong sideYo: Yarn over

# Instructions for Making the Bernat In The Details Knit Hoodie Pattern:

#### Back

- **Cast on** 42 (44-46-48) sts.
- Work in garter st (K every row), noting the 1st row is WS.
- Cont for 9½ (10-10½-11)" [24 (25.5-26.5-28) cm] from Beg, ending on a RS row.
- Cast off.

#### **Pocket Linings (make 2)**

- **Cast on** 15 (15-17-17) sts.
- Work 2" [5 cm] in stocking st, ending on a purl row.
- **Dec** 1 st at center of last row.
- You will have 14 (14-16-16) sts rem.
- Leave sts on a spare needle.

#### **Right Front**

- Cast on 23 (24-25-26) sts.
- Work in garter st, noting 1st row is WS, for 2½" [6.5 cm], ending on a WS row.
- **Place pocket:** Next row: (RS). **K7**. Slip next 14 (14-16-16) sts onto a st holder. K14 (14-16-16) from Pocket Lining. K2 (3-2-3).
- Cont in garter st until work from Beg measures 8½ (9-9½-10)" [21.5 (23-24-25.5) cm], ending on a WS row.
- Shape neck:
  - o Next row: (RS). **Cast off** 3 (4-5-5) sts. K to end of row. You will have 20 (20-20-21) sts rem.
  - o Next row: K.
  - o Next row: **Cast off** 3 sts. K to end of row.
  - o **Rep** last 2 rows twice more. You will have 11 (11-11-12) sts rem.
- Cont in garter st until work measures same length as Back, ending on a WS row.
- Cast off.
- Place markers for buttons ½" [1.25 cm], 2" [5 cm], and 3½" [9 cm] down from neck edge; buttons should be spaced 1½" [4 cm] apart.

#### **Left Front**

- Note: Work buttonhole row as follows to correspond to button markers on Right Front: (RS). K to last 4 sts. **K2tog. yo. K2**.
- Cast on 23 (24-25-26) sts.
- Work in garter st for 2½" [6.5 cm], noting 1st row is WS and ending on a WS row.
- **Place pocket:** Next row: (RS). K2 (3-2-3). Slip next 14 (14-16-16) sts onto a st holder. K14 (14-16-16) from Pocket Lining. K7.
- **Cont** in garter st, working buttonhole rows to correspond with Right Front button markers, until work from Beg measures 8½ (9-9½-10)" [21.5 (23-24-25.5) cm], ending on a RS row.
- Shape neck:
  - o Next row: (WS). **Cast off** 3 (4-5-5) sts. K to end of row. You will have 20 (20-20-21) sts rem.
  - o Next row: K.
  - Next row: **Cast off** 3 sts. K to end of row.
  - o Next row: K.
  - o **Rep** last 2 rows twice more. You will have 11 (11-11-12) sts rem.
- Cont in garter st until work measures same length as Back, ending on a WS row.
- Cast off.

#### **Sleeves**

- Cast on 32 (34-36-38) sts.
- Work in garter st, noting 1st row is WS, for 7 (7½-8-9)" [18 (19-20.5-23) cm], ending on a RS row.
- Cast off.

#### Hood

- Panel Pat (worked over 15 sts):
  - o **1st row:** (RS). P2. (Wrap 3. K1) twice. Wrap 3. P2.
  - o **2nd row:** K2. P11. K2.
  - o **3rd row:** P2. K2. Wrap 3. K1. Wrap 3. K2. P2.
  - **4th row:** As 2nd row.
  - These 4 rows form Panel Pat.
- Sew shoulder seams.
- With RS facing and a circular needle, **pick up and K** 15 (17-19-19) sts evenly up Right Front neck edge, 19 (21-23-23) sts across Back neck edge (placing st marker on center back st), and 15 (17-19-19) sts evenly down Left Front neck edge. You will have 49 (55-61-61) sts.
- Foundation row: (WS). K4. P11. K19 (25-31-31) (slipping marker on center back st). P11. K4.
- Hood Shaping:
  - o **1st row:** K2. Work 1st row of Panel Pat across next 15 sts. Place marker between sts. K to center marked st. **M1**. K marked st. **M1**. K7 (10-13-13). Place 2nd marker between sts. Work 1st row of Panel Pat across next 15 sts. K2.
  - 2nd row: K2. Work 2nd row of Panel Pat across next 15 sts. Slip marker. K to marked st. Purl marked st. K to 2nd marker. Work 2nd row of Panel Pat across next 15 sts. K2.
  - o **3rd row:** K2. Work 3rd row of Panel Pat across next 15 sts. Slip marker. K to center marked st. K marked st. K to 2nd marker. Work 3rd row of Panel Pat across next 15 sts. K2.
  - o **4th row:** As 2nd row.
  - 5th row: K2. Work 1st row of Panel Pat across next 15 sts. Slip marker. K to center marked st. M1. K marked st. M1. K to 2nd marker. Work 1st row of Panel Pat across next 15 sts. K2.
  - Keeping Cont of Panel Pat, Rep 2nd to 5th rows 3 times more. You will have 59 (65-71-71) sts.
  - Cont even in Pat (keeping center back st in stocking st) until Hood from pick up edge measures approx 8 (8½-8½-9)" [20.5 (21.5-21.5-23) cm], ending on a WS row.
  - o Cast off. Sew top Hood seam.

### **Finishing**

- Pocket Edging:
  - o With RS facing, **K14** (14-16-16) from Pocket st holder.
  - o K2 rows (garter st).
  - o Cast off knitways (WS).
- Assembly:
  - o Sew sides of Pocket Edging in position on RS.
  - Sew edges of Pocket Linings in position on WS.

- $\circ$  Place markers on side edges 3¾ (4-4¼-4½)" [9.5 (10-11-11.5) cm] down from shoulders.
- o Sew in sleeves between markers.
- o Sew side and sleeve seams.
- o Sew buttons to correspond to buttonholes.